

Waterco FPI Valves

Engineered for optimal performance



Waterco FPI Valves are designed for optimal hydraulic flow and engineered to be maintenance free.

- Teflon™ seals*
- Quick installation
- UPVC and ABS construction
- Available in 2 and 3 way configurations
- 316 grade stainless steel components
- Up to 600 kPa pressure rated



Waterco FPI Valves

Teflon seals*

Teflon™ seals offer minimal friction and smooth operation.

Quick installation

The FPI valve body is made from UPVC. Its compatibility with PVC pipes will ensure quick setting and a stronger bond.

Engineered strength

Both the FPI Valve lid and handle are constructed from premium ABS plastic. The valve's steel components are constructed from high quality 316 grade stainless steel.

High pressure rating

Its advanced design and construction enable the FPI valves to withstand a working pressure of 400 to 600 kPa depending on the model selected.

Optional half unions

25/32mm and 65/80mm valves are available with the option of half unions for ease of installation and maintenance.

Warranty

FPI valves are covered by a 12 month warranty against faulty materials and workmanship.



2 way 40/50mm slip fit valve



3 way 40/50mm slip fit valve



3 way 25/32mm slip fit valve



3 way 25/32mm valve threaded with half unions.



2 way 50/65mm slip fit valve



3 way 50/65mm slip fit valve

Specifications

Product Code	Description	Nominal Size	Teflon Seals	Pressure Rating
148503	2 way valve threaded with half unions	25/32 mm	✓	600 kPa
148505	2 way valve slip fit	25/32 mm	✓	600 kPa
148500	3 way valve threaded with half unions	25/32 mm	✓	600 kPa
148502	3 way valve slip fit	25/32 mm	✓	600 kPa
14852	2 way valve slip fit	40/50 mm	✓	400 kPa
14853	3 way valve slip fit	40/50 mm	✓	400 kPa
14856	2 way valve slip fit	50/65 mm	✓	400 kPa
14860	3 way valve 360° slip fit	50/65 mm	✓	400 kPa
14882	2 way valve slip fit	65/80 mm	✓	400 kPa
14892	2 way valve threaded with half unions	65/80 mm	✓	400 kPa
14883	3 way valve slip fit	65/80 mm	✓	400 kPa
14893	3 way valve threaded with half unions	65/80 mm	✓	400 kPa
148564	2 Way Valve Actuated Type (4 Bar)	50/65mm	✓	400 kPa
148584	3 Way Valve Actuated Type (4 Bar)	50/65mm	✓	400 kPa

*™ Teflon is a Registered Trade Mark of DuPont Corporation

OFFICES - AUSTRALIA

NSW - Sydney (Head Office)
Tel: +61 2 9898 8600

QLD - Brisbane
Tel: +61 7 3299 9900

VIC/TAS - Melbourne
Tel: +61 3 9764 1211

WA - Perth
Tel: +61 8 9273 1900

SA/NT - Adelaide
Tel: +61 8 8244 6000

ACT Distribution
Tel: +61 2 6280 6476

OFFICES - OVERSEAS

Waterco (Europe) Limited
Sittingbourne, Kent, UK
Tel: +44 (0) 1795 521 733

Waterco (USA) Inc
Augusta, Georgia, USA
Tel: +1 706 793 7291

Waterco Canada
St Hyacinthe, Quebec, Canada
Tel: +1 450 796 1421

Waterco (NZ) Limited
Auckland, New Zealand
Tel: +64 9 525 7570

Waterco (C) Limited
Guangzhou, China
Tel: +86 20 3222 2180

Waterco (Far East) Sdn Bhd
Selangor, Malaysia
Tel: +60 3 6145 6000

PT Waterco Indonesia
Jakarta, Indonesia
Tel: +62 21 4585 1481

Waterco Singapore Intl Pte Ltd
Nehsons Building, Singapore
Tel: +65 6344 2378

DISTRIBUTED BY:

WATERCO
Water, the liquid of life

